HD30491
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	500 - 2500 MHz	
Power Output Psat	15 Watt Min	CW
Output Power @ P1dB	6 Watt Min	
Power Gain	42 dB Min	
Gain Flatness	3 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	32dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	28 VDC Nom	
Current Consumption	2.3 Amp Max	At rated Pout
Max Input Power	+8 dBm	<10 Sec without damage
Load VSWR Protection	∞ : 1	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	125 x 63 x 27 mm	Without connectors
Weight	450 gr.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	N/C
2	REV	N/C
3	CURRENT SENSOR	I_D@100mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUDOWN	TTL
6, 7	VDD	28VDC
8, 9	GND	Ground

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com

HD30491
SOLID STATE HIGH POWER AMPLIFIER


OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com

HD30491
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING SHOWN WITH HEATSINK



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com