HD30963
SOLID STATE HIGH POWER PULSE AMPLIFIER

FEATURES

High peak power S-Band pulse applications
High power advanced GaN pulse devices
Instantaneous bandwidth
Suitable for linear pulse applications
Built-in control, monitoring and protection circuits
High efficiency, reliability and ruggedness

ELECTRICAL SPECIFICATIONS Relative to 50Ω

Parameter	Specification			Notes
Operating Frequency Range	2.7 - 2.9 GHz			
Peak Output Power	8 KWatt Min			
Pulse Characteristics (Max Rating)	**Duty**	**Width**	**PRF**	
	10 %	150 µSec	0 - 2 KHz	
Rise / Fall Time	<50 nS			10% to 90%
Input Peak Power for Nominal Output	0 dBm ±1.0dB Nom			Power Gain = 69 dB Nom
Harmonics	-30 dBc Max			
Spurious	-70 dBc Max			
Power flatness	≤1.0 dB			Over operating frequency
Pulse Width Variation (Jitter)	<-70 nS			
Amplitude Pulse Droop	≤0.5 dB for 150 µSec Pulse ≤0.1 dB for 10 µSec Pulse			
Amplitude Ripple	≤0.3 dB			
Phase change along the pulse	≤35°, 0 ≤ t ≤ 5 µSec ≤50°, 5 ≤ t ≤ 100 µSec			
Phase ripple along the pulse	≤1°			
Pulse to pulse phase stability	<0.018°			
Pulse Amplitude Stability	<0.0027 dB			
Input / Output VSWR	1.5 : 1 Min			
Pulse Phase Noise	≤100 dBc/Hz @ 1 KHz from carrier			
System Efficiency	15 % Min			

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	14 U	Without cabinet
Weight	115 Kg. Max	Including cabinet
RF Connectors In/Out	Type N-F / Waveguide WR284	Front Panel Standard
RF Output Monitoring FWD / REV	Type N-F	
AC Power	380/220 VAC, 48-64Hz, 3 Phase & Natural	4 Wires
Interface Connector	TBD	
Monitor & Control - **OPTIONAL Interface**	1 Ethernet RJ-45 circular connector TCP/IP 1 RS422/485 D-dub 9S port for redundancy	Remote Bluetooth application
Cooling	Built in forced air	

HD Communications Corp.
332-C Dante Court, Holbrook, NY 11741
Tel: (631) 588-3877 Fax: (631) 648-0518 Email: sales@hdcom.com
© COPYRIGHT 2008-2017 HD Communications Corp.
All rights reserved. Redistribution or republication of these pages in any form requires express written consent.

HD30963
SOLID STATE HIGH POWER PULSE AMPLIFIER

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	-20 to +55°C	
Storage Temperature	-40 to +70°C	
Relative Humidity	95% @ 40°C	Non Condensing
Shock & Vibrations	MIL STD 810E	
EMI/EMC	MIL STD 461E	
Cabinet Emitted Radiation	Residual RF radiation < 5mW/cm^3	Continuous 8 hours exposure

OUTLINE DRAWING (for illustration only)



HD Communications Corp.
332-C Dante Court, Holbrook, NY 11741
Tel: (631) 588-3877 Fax: (631) 648-0518 Email: sales@hdcom.com
© COPYRIGHT 2008-2017 HD Communications Corp.
All rights reserved. Redistribution or republication of these pages in any form requires express written consent.