# HD31030
# SOLID STATE HIGH POWER AMPLIFIER

**PRELIMINARY**

**FEATURES**

Class AB linear LDMOS design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness




**ELECTRICAL SPECIFICATIONS**

| Parameter | Specification | Notes |
|---|---|---|
| Operating Frequency Range | 922 MHz | |
| Power Output Psat | 100 Watt Min | CW |
| Power Gain | 20 dB Min | |
| Input Return Loss | 10 dB Min | Relative to 50 Ohm |
| 2-Tone Intermodulation (IMD) | >30 dBc Typ | 40dBm/Tone, Δ = 1MHz |
| Harmonics | >20 dBc Typ | At rated Pout |
| Non Harmonics Spurious | >60 dBc | |
| Operating Voltage | 27 - 29 VDC | |
| Current Consumption | 8 Amp Max | At rated Pout |
| Max Input Power | 1.5 Watt | Without damage |
| Load VSWR Protection | ∞ : 1 | |
| Turn On / Off Speed | 5 µSec Max | |

**ENVIRONMENTAL CHARACTERISTICS**

| Parameter | Specification | Notes |
|---|---|---|
| Operating Case Temperature | -20 to +75 °C | |
| Storage Temperature | -40 to +85 °C | |
| Relative Humidity | 5 to 95 % | Non Condensation |

**MECHANICAL SPECIFICATIONS**

| Parameter | Specification | Notes |
|---|---|---|
| Dimensions | 147 X 69 X 27 mm | Excluding Connectors |
| Weight | 400 g. | Typical Weight |
| RF Connectors In/Out | SMA female | |
| DC Power / Interface Connector | 9-Pin D-Sub | |
| Cooling | External Heatsink | Forced air required |

**D-SUB CONNECTOR PIN ASSIGNMENT**

| Pin | Function | Description |
|---|---|---|
| 1 | FWD | N/C |
| 2 | REV | N/C |
| 3 | CURRENT NONITOR | $I_D$@20mV/100mA Typ |
| 4 | TEMP SENSOR | $V_T$@10mV/°C + 500mV Typ |
| 5 | SHUTDOWN | TTL |
| 6, 7 | VDD | 28VDC |
| 8, 9 | GND | Ground |


**332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518**
sales@rfamplifiers.com www.rfamplifiers.com

Communications Corp.

# HD31030
# SOLID STATE HIGH POWER AMPLIFIER

**PRELIMINARY**

## OUTLINE DRAWING





**332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518**
sales@rfamplifiers.com www.rfamplifiers.com