HD Communications Corp.

HD31214
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Rack mount system
Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	3.0 - 6.0 GHz	
Power Output @ Psat	70 Watt Typ	CW
Power Output @ P1dB	40 Watt Min	CW
Power Gain	47 dB Min	
Power Gain Flatness	3.0 dB p-p	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	37dBm/Tone, Δ = 1MHz
Harmonics	>20 dBc Typ	At rated output power
Non Harmonics Spurious	>60dBc	
Operating Voltage	100 - 240 VAC	Single phase
Power Consumption	300 Watt Max	At Rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	∞ : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U
Weight	20 kg.	
RF Connectors In/Out	Type-N Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com

HD31214
SOLID STATE HIGH POWER AMPLIFIER

Communications Corp.

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com