HD31240
SOLID STATE HIGH POWER AMPLIFIER

Communications Corp.

FEATURES

Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	500 - 1500 MHz	
Power Output Psat	25 Watt Min	CW
Power Gain	44 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	34dBm/Tone, Δ = 1MHz
Harmonics	>20 dBc Typ	At rated output
Non Harmonics Spurious	>60 dBc	
Operating Voltage	28 VDC Nom	
Current Consumption	3 Amp Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	∞ : 1	
Turn On / Off Speed	5 µSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	Option 000: 147 X 69 X 27 mm Option 101: 170 X 69 X 27 mm	Excluding Connectors
Weight	550 gr.	Max Weight
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	Option-101 - Analog Forward Power Indicator
2	REV	Option-103 - Analog Gain Control
3	CURRENT SENSOR	I_D@100mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	TTL
6, 7	VDD	28VDC
8, 9	GND	Ground

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
sales@rfamplifiers.com www.rfamplifiers.com

HD31240
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
sales@rfamplifiers.com www.rfamplifiers.com