HD31261
SOLID STATE HIGH POWER AMPLIFIER

FEATURES
Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	0.8 - 4.2 GHz	
Power Output CW	100 Watt Min	-0.3dB lower @ 4.0-4.2GHz
Power Output @ P1dB GCP	40 Watt Min	CW
Power Gain	50 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input / Output Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30dBc Typ	40 dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	32 VDC Nom	
Current Consumption	16 Amp Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	220 x 144 x 27 mm	Excluding connectors
Weight	1.7 Kg.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	OPTION 103 - Max Gain @ 0VDC or Open; Min Gain @ 5VDC
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	Enable = TTL “Hi” or Open; Disable = TTL “Lo” or Short
6, 7	VDD	32VDC
8, 9	GND	Ground

HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com

HD31261
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com