HD31274
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN design
Instantaneous ultra-wide bandwidth
Suitable for all Single channel modulation standards
Small form factor & light weight
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 6.0 GHz	
Power Output	50 Watt Min / 70 Watt Typ	CW
Power Output @ P1dB	25 Watt Typ	20 Watt @ 1.0-1.5 GHz
Power Gain	47 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input / Output Return Loss	-10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	37 dBm/Tone, Δ = 1 MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	28 - 30 VDC	
Current Consumption	12 Amp Max / <10 Amp Typ	At rated Pout
Input Power Protection	+8 dBm Max	10 Sec Without damage
Load VSWR Protection	∞ : 1	1 minute @ rated output
Turn On / Off Speed	5 µSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	230 x 106 x 27 mm	Excluding connectors
Weight	1.25 Kg.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9 Pin D-Sub	
Cooling	External Heatsink	Forced air required


D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	N/C
2	VVA	N/C
3	CURRENT SENSOR	I_D@20mV/100mA Typ
4	TEMP SENSOR	V_T@10mV/°C + 500mV Typ
5	SHUTDOWN	TTL - Optional 5µS switching speed
6, 7	VDD	30VDC
8, 9	GND	Ground

HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com

HD31274
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



HD Communications Corp. 338 Jericho Tpke. Ste 387
Syosset, NY 11791
Tel: (631) 588-3877 Email: sales@hdcom.com