
HD31989
SOLID STATE HIGH POWER AMPLIFIER

Communications Corp.



FEATURES

Class AB linear hybrid GaAs and GaN design
Instantaneous ultra-wide bandwidth
Suitable for all single channel modulation standards
Suitable for S, X and Ku band applications
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	6.0 - 18.0 GHz	
Power Output at Psat	50 Watt Min	CW
Power Output at P1dB	20 Watt Typ	
Power Gain	47 dB Min	
Power Gain Flatness	4.0 dB p-p Max	
Input Return Loss	10 dB Min	
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Noise Figure	10 dB Max	
Operating Voltage	32 VDC Nom	
Current Consumption	15 Amp Max	At rated Pout
Input Power Protection	+3 dBm Max	<10 Sec without damage
Load VSWR Protection	3 : 1 Max	<1 minute @ rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +65°C	
Storage Temperature	-40 to +85°C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	180 x 200 x 27 mm / (7.09 x 7.87 x 1.06 inch)	Excluding connectors
Weight	5.15 Kg	
RF Connectors In/Out	SMA female	Cover Flange
DC Power / Interface Connector	7-Pin Hybrid D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT


Pin	Function	Description
1	GND	Ground
2	N/C	N/A
3	Current Sensor	I_D@20mV/100mA Typ
4	Temp. Sensor	V_T@10mV/°C + 500mV Typ
5	Shutdown	Enable = TTL “Hi” or open / Disable = TTL “Lo” or short
A1	VDD	32VDC
A2	GND	Ground

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com

HD31989
SOLID STATE HIGH POWER AMPLIFIER

Communications Corp.

OUTLINE DRAWING



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfamplifiers.com www.rfcomp.com sales@hdcom.com