HD32079
SOLID STATE HIGH POWER AMPLIFIER

HD Communications Corp.

FEATURES

Rack mounted system
Ultra-broadband MMIC hybrid design
Instantaneous ultra-wide bandwidth
Suitable for all single channel modulation standards
Built-in protection circuits
Optional uP remote control & monitoring
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	2.0 - 20.0 GHz	
Power Output CW	20 Watt Min	CW across 2-20GHz
Power Output @ P1dB	8 Watt Typ	
Power Gain	43 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	33dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated Pout
Non-Harmonic Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	90 - 260 VAC	
Power Consumption	300 Watt Max	At rated Pout
Max Input Power Protection	+5 dBm	<10 Sec without damage
Load VSWR Protection	5 : 1	<1 minute Sec without damage

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 562 mm	3U, excluding handles
Weight	20 Kg.	
RF Connectors In/Out	Hi Freq. SMA-F / SMA-F	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Controller will reduce output power by up to 1.5dB.

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com

HD Communications Corp.

HD32079
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING – Shown with Optional LCD Controller



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com