HD Communications Corp.

HD32153
SOLID STATE HIGH POWER AMPLIFIER



FEATURES

Ku-Band high power CW applications
Rack mounted system
Linear high power GaN design
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	14.0 - 14.6 GHz	Nominal
Power Output @ Psat	150 Watt Min	CW
Power Gain	52 dB Min	
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
Harmonics	-30 dBc Max	At rated output
Non-Harmonic Spurious	-60 dBc Max	
Operating Voltage	100 - 240 VAC	
Power Consumption per Duty Cycle	1800 WattMax	At rated output
Max Input Power Protection	+3 dBm	<10 Sec without damage
Load VSWR Protection	∞ : 1	Output isolator

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	4U rack mount	Per outline drawing
Weight	30 Kg. Max	
RF Connectors In/Out	Type-N Female / WR62	Front Panel Standard
AC Power	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	

332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com

Communications Corp.

HD32153
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING - With LCD Controller Option




332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com

HD Communications Corp.

HD32153
SOLID STATE HIGH POWER AMPLIFIER

- 5U System Outline (Rear Connectors Input N, Output N)



332C Dante Ct. Holbrook, NY 11741 Phone: 631-588-3877 Fax: 631-648-0518
www.rfcomp.com www.rfamplifiers.com sales@hdcom.com