HD Communications Corp.

HD33770
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN design
Instantaneous C-Band bandwidth
Rack mounted system
Designed for broadband EMI/RFI, Lab, Comm. and EW applications
Suitable for all single channel modulation standards
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	6.0 - 8.0 GHz	
Power Output @ Psat	100 Watt Min	CW
Power Output @ P1dB	50 Watt Min	CW
Power Gain	50 dB Min	
Power Gain Flatness	3.0 dB p-p	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	40dBm/Tone, Δ = 1MHz
Harmonics	<-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	Single phase
Power Consumption	1000 Watt Max	At Rated Pout
Input Power Protection	+5 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U - excluding handles
Weight	20 kg.	
RF Connectors In/Out	Type-N Female	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Optional Remote Bluetooth application

338 Jericho Turnpike, Unit 387. Syosset, NY 11791 sales@hdcom.com
www.rfamplifiers.com www.rfcomp.com

HD Communications Corp.

HD33770
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWONG - SHOWN WITH OPTIONAL LCD AND DIGITAL CONTROLLER



338 Jericho Turnpike, Unit 387. Syosset, NY 11791 sales@hdcom.com
www.rfamplifiers.com www.rfcomp.com